



0205700 / TB21 – 0205701 / TB22 – 0205722-0205725 / TB2S 0205711 / TB21B

WASTE FOR SHOWER TRAY Ø90 Turb@flow® 2

FUNCTION :

- Trapped waste for shower trays with ø90 mm hole
- Adapted to ultra-flat shower trays
- Swivelling outlet to bond or screw Ø40

DESCRIPTION :

- Body : co-injected with built-in seals.
- Inner traps : removable, with hair catcher
- Swivelling outlet : horizontal : 30° - vertical (downwards) : 20°



CODE NUMBER	COVER	SCREW FOR CLAMP	KEY
0205700 / TB21	ABS CHROME	COVER FIXING WITH HIGH HEAD + O-RING	HIGH HEAD KEY
0205701 / TB22	METAL CHROME	COVER FIXING WITH HIGH HEAD + O-RING	HIGH HEAD KEY
0205711 / TB21B	ABS GLOSS WHITE	COVER FIXING WITH HIGH HEAD + O-RING	HIGH HEAD KEY
0205722-725 / TB2S	WITHOUT COVER	NO COVER SETTING WITH LOW HEAD	LOW HEAD KEY

TECHNICAL FEATURES :

- Materials :
 - Co-injected body : polypropylene and elastomere seals.
 - Co-injected spherical connection : polypropylene + ABS
- Dimensions :
 - Compactness : 80 mm.
 - Water seal height : 50 mm
 - Connection to the waste pipe : compression G1"1/2 – or to be glued : ø40 mm.
 - Tightening thickness : 1 to 25 mm
- Flow rate : 43 l/min under a 15 mm water load

NF CERTIFIED :

- NF 077 - EN 274



ACCESSORIES SUPPLIED :

- Key / plug :
 - Clamping tool with torque limiter (the installer is liable for the use of another tool)
 - Keeps the trap clean during installation

INSTALLATION :

- Swivelling outlet ;
- For connection to the waste pipe : compression or to be glued ;
- Calibrated clamp

MAINTENANCE :

- The use of aggressive cleaners is prohibited.
- Removable inner traps : access to the waste pipe with a Ø 15 mm snake



Turb@flow® 2

WATER SEAL

50

132



0205700 / TB21 – 0205701 / TB22 – 0205722-0205725 / TB2S
0205711 / TB21B
WASTE FOR SHOWER TRAY Ø90 Turb@flow® 2

0205722 / TB2S
0205725 / TB2S

